



# TECHNICAL DATA SHEET

---

## CPP 0124 – FAST SYNTHETIC THINNER

### DESCRIPTION

FAST SYNTHETIC THINNER is a top quality thinner suitable for use with most single pack polyurethane finishes.

It may be used where small areas or complete vehicles are to be painted.

### MIXING

Approximately 10-20% FAST SYNTHETIC THINNER should be added, the amount may be varied slightly if the user wishes to do so to meet certain requirements.

### FLASH POINT

Below 22°C

### STORAGE

Unmixed, correctly stored material, in firmly closed original containers, has a shelf-life of over 1 year. Contents of opened containers should be used up quickly. Always replace cap immediately after use.

### HEALTH & SAFETY

Please refer to relevant Health and Safety Data Sheet, reference no. HSD 0124.

### NOTE

This data relates only to the product designated herein and does not apply to use in combination with any other materials or in any other process.

The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.

Our product range is under continuous development and therefore products and specifications are subject to change without notice.

This product is for professional use only.

All trademarks, registered trademarks, brands and product names respected.

---

#### Churchill Paints Ltd.

Riverdane Rd, Eaton Bank Trading Estate, Congleton, Cheshire, United Kingdom

T: +44 (0)1260 290 666

F: +44 (0)1260 290 444

✉: [sales@churchill-paints.co.uk](mailto:sales@churchill-paints.co.uk)

Website: <http://www.churchill-paints.com>

© CHURCHILL PAINTS 1994