

# TECHNICAL DATA SHEET

---



## CPP 0132 – 2K SLOW THINNER

### **DESCRIPTION**

2K - SLOW THINNER is a top quality thinner designed for use with a wide range of 2K paints, primers and clear coats. Where slow drying is required.

### **MIXING**

Mix in proportions specified on the Paint/Clear coat/Primer Technical information sheet. Stir well and strain before use.

### **FLASH POINT**

22`C -32`C

### **STORAGE**

Unmixed, correctly stored material, in firmly closed original containers, has a shelf-life of over 1 year. Contents of opened containers should be used up quickly.

### **HEALTH & SAFETY**

Please refer to relevant Health and Safety Data Sheet, reference no. HSD 0132.

### **NOTE**

This data relates only to the product designated herein and does not apply to use in combination with any other materials or in any other process.  
The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.  
Our product range is under continuous development and therefore products and specifications are subject to change without notice.  
This product is for professional use only.  
All trademarks, registered trademarks, brands and product names respected.

---

#### **Churchill Paints Ltd.**

Riverdane Rd, Eaton Bank Trading Estate, Congleton, Cheshire, United Kingdom

T: +44 (0)1260 290 666

F: +44 (0)1260 290 444

✉: [sales@churchill-paints.co.uk](mailto:sales@churchill-paints.co.uk)

Website: <http://www.churchill-paints.com>

© CHURCHILL PAINTS 1994