



INDUSTRIAL CELLULOSE READY MIXED COLOUR

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006

FOR PROFESSIONAL USE ONLY

Version: 01

Revision: 17.05.2012

Print date: 21.05.2012

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- 1.1 **Product Name:** INDUSTRIAL CELLULOSE READY MIXED COLOUR
Product Code: 0670, 0676, 0677, 0678, 0679
Product General Name: Topcoat
- 1.2 **Intended use:** Industrial
- 1.3 **Producer/Supplier:** Churchill Paints Ltd
Riverdane Road, Eaton Bank Trading Estate,
Congleton, Cheshire, CW12 1PN
Tel. +44(0)1260 290666, Fax. +44(0)1260 290 444
Email: sds@churchill-paints.co.uk
- 1.4 **Emergency Phone:** In case of health hazard, seek medical attention
For additional information please call: +44(0) 1260 290 666 (office hours only)

2. HAZARDS IDENTIFICATION

Hazards of the Mixture (Preparation) identified in section 1:

Hazard Symbols:



- Risk Phrases:**
- R11 Highly Flammable
 - R20/21 Harmful by inhalation and in contact with skin
 - R36/37/38 Irritating to eyes, respiratory system and skin

OTHER INFORMATION:

Vapours of the product are heavier than air and may accumulate on the ground, in the sump of pits, drains or cellars with higher concentrations. Ground level ventilation is recommended.



INDUSTRIAL CELLULOSE READY MIXED COLOUR

3. COMPOSITION / INFORMATION ON INGREDIENTS

Substances in the Mixture (Preparation) presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC, or subject to recognised exposure limits:

Chemical name	%	CAS No.	EC No. (EINECS)	Index No.	Symbol abbreviation	Risk phrases
n-Butyl Acetate Butyl ethanoate	25--50	123-86-4	204-658-1	607-025-00-1		R10, R66, R67
Toluene	10--25	108-88-3	203-625-9	601-021-00-3	F; Repr. Cat. 3; Xn; Xi;	R11, R38, R48/20, R63, R65, R67
Xylene (mixture of isomers)	2.5--10	1330-20-7	215-535-7	601-022-00-9	Xn, Xi	R10, R20/21, R38
Acetone; propan-2-one; propanone	0--25	67-64-1	200-662-2	606-001-00-8	F, Xi,	R11, R36, R66, R67
propan-2-ol; isopropyl alcohol; isopropanol	0--2.5	67-63-0	200-661-7	603-117-00-0	F, Xi	R11, R36, R67
2-methylpropan-1-ol; iso-butanol	1--2.5	78-83-1	201-148-0	603-108-00-1	Xi	R10, R37/38, R41, R67

4. FIRST AID MEASURES

General:	In all cases of doubt, or where symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation:	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
Eye contact:	Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart, and seek medical advice.
Skin contact:	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners
Ingestion:	If accidentally swallowed, obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE – FIGHTING MEASURES

Extinguishing media: Recommended: alcohol-resistant foam, CO₂, Dry powder, Sand.
Do not use water jet.



INDUSTRIAL CELLULOSE READY MIXED COLOUR

Recommendations: Fire will produce dense black smoke. Exposure to decomposition products (see section 10) may cause a health hazard. Appropriate breathing apparatus should be worn. Water-mist may be used to cool closed containers.
Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

Environmental precautions: Do not allow to enter drains or water courses. If the product enters drains or sewers, inform water authorities in accordance with local regulations.

Cleaning up: Preferably clean with a detergent. Avoid using solvents.

7. HANDLING AND STORAGE

7.1 Handling: Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, earth the container and connect to the receiving container with a bonding strap. Operators should wear antistatic footwear and clothing. Floors should be of the conducting type.
Isolate from sources of heat, sparks and flame. No sparking tools should be used.
Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in areas of storage and use.
For personal protection, see Section 8.
Never use pressure to empty, the container is not a pressure vessel. Always keep in containers made of the same material as the original supply container.
Good housekeeping standards and regular safe removal of waste materials will minimise risks of spontaneous combustion and other fire hazards.
Always comply with the Health and Safety at Work Etc. Act.
The Manual Handling Operations Regulations 1992 (GB and NI) may apply to the handling of containers of this product. Refer to the published guide weight when carrying out Dry assessments.

7.2 Storage: Store in accordance with The Dangerous Substances and Explosive Atmospheres Regulations 2002.
Observe label precautions. Store between 5 and 30 degrees C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and stored upright to prevent leakage.
Store separately from oxidising agents, strong alkalis & strong acids



INDUSTRIAL CELLULOSE READY MIXED COLOUR

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Workplace Exposure Limits (WELs):

Ingredient name:	Comment (from EH40)	Time-weighted average – 8 hrs (TWA).		Short-term exposure limits –15min (STELs)	
		ppm.	mg/m ³	ppm.	mg/m ³
n-Butyl Acetate		150	724	200	966
Toluene	Sk	50	191	100	384
Xylene	Sk	50	220	100	441
Acetone; propan-2-one; propanone		500	1210	1500	3620
propan-2-ol; isopropyl alcohol; isopropanol		400	999	500	1250
2-methylpropan-1-ol; iso-butanol		50	154	75	231

Comments from HSE Guidance Note EH40/2005 Workplace exposure limits:

Sk : Can be absorbed through skin

8.2 Exposure controls:

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

8.2.1 Occupational exposure controls:

All personal protective equipment must meet the requirements of the COSHH Regulations.

Respiratory protection: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, welding and/or flame cutting of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Further information on respiratory protective equipment is available from the HSE website.

Hand protection:

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection, and should not be applied once exposure has occurred.



Protective gloves



INDUSTRIAL CELLULOSE READY MIXED COLOUR

Eye protection: Eye protection designed to protect against liquid splashes should be worn.



Skin protection: Personnel should wear antistatic and fire resistant clothing. Contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

8.2.2 Environmental exposure controls:

Do not allow to enter drains or watercourses.

9. PHYSICAL AND CHEMICAL PROPERTIES

(General Information)	
Physical State:	Liquid
Colour:	According to product specification
Odour:	Characteristic
Density (kg/L):	Not determined
Vapour density:	> air
Viscosity:	480" BSB4 Flow Cup @ 20°C
pH:	N/A
VOC content:	
Flash point:	7°C
Explosion limits:	
Lower (by vol):	1.4 %
Upper (by vol):	
Solubility in / Miscibility with water:	NOT MISCIBLE

10. STABILITY AND REACTIVITY

10.1 Stability: Stable under recommended storage and handling conditions (see Section 7). In a fire, hazardous decomposition products may be produced. These may include Carbon Monoxide, Carbon Dioxide, Smoke & Oxides of Nitrogen.

10.2 Reactivity: Keep away from oxidising agents, strong alkalis and strong acids to prevent the possibility of exothermic reactions.

**INDUSTRIAL CELLULOSE READY MIXED COLOUR****11. TOXICOLOGICAL INFORMATION**

There is no data available on the mixture itself.

Exposure to organic solvent vapours above the OEL's may result in adverse health effect such as irritation of the mucous membrane and respiratory system and adverse effect on kidney, liver and central nervous system. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness, and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the product may lead to removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible local damage.

12. ECOLOGICAL INFORMATION

There is no data available on the mixture itself.

Do not allow the product to enter drains or watercourses.

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

13. DISPOSAL CONSIDERATIONS

Do not allow the product to enter drains or watercourses.

Residues in emptied containers should be neutralised with decontaminant (see Section 6). Wastes, including empty containers, are controlled wastes and should be disposed of in accordance with:

- Control of Pollution Act 1974
- Environmental Protection Act

and should be recycled or disposed of through a licenced waste management facility.

14. TRANSPORT INFORMATION

Transport only in accordance with CHIP (Great Britain) or ADR (rest of Europe) for road. RID for rail. IMDG for sea and ICAO/IATA for air transport.

Land - road/railway:

UN number: UN1263
Transport document name: Paint Related Material
ADR/RID Class: 3
Packing group: II

ADR/RID Label:**Sea:**

UN Number: UN1263
Proper Shipping Name: Paint Related Material
IMDG Class: 3.2
Packing Group: II



INDUSTRIAL CELLULOSE READY MIXED COLOUR

IMDG Label:



Marine pollutant: No
Emergency schedules (EmS): 3-05

Air: – UN/IATA

UN number: UN1263
Proper Shipping Name: Paint Related Material
ICAO/IATA Class: 3
Packing Group II
ICAO/IATA Label:



15. REGULATORY INFORMATION

This product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows:

Hazard symbol(s):



(Xn)
Harmful



(F)
Highly Flammable

Contains: Toluene

Risk Phrases: R11 Highly Flammable
R20/21 Harmful by inhalation and in contact with skin
R36/37/38 Irritating to eyes, respiratory system and skin

Safety phrases: S16 Keep away from sources of ignition - No smoking
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S38 In case of insufficient ventilation wear suitable respiratory equipment
S51 Use only in well-ventilated areas

Additional warning phrases: For use in industrial installations only

**INDUSTRIAL CELLULOSE READY MIXED COLOUR****FOR PROFESSIONAL USE ONLY!**

The information contained in this Safety Data Sheet does not constitute the user's own assessment of the workplace risks, as required by other health & safety legislation. The provisions of the Health & Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

16. OTHER INFORMATION

Full text of risk phrases appearing in Section 3:

R10	Flammable
R11	Highly flammable
R20/21	Harmful by inhalation and in contact with skin
R36	Irritating to eyes
R37/38	Irritating to respiratory system and skin
R38	Irritating to skin
R41	Risk of serious damage to eyes
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R63	Possible risk of harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

The information contained in this safety data sheet is based on the state of knowledge and national legislation at the time of the 'revision date' shown on page 1. Further updates to this safety data sheet, in line with changes to legislation and technical knowledge, will be available from Churchill Paints or the Churchill website. Contact Churchill Paints for the latest revision. This safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. It is the user's responsibility to ascertain the suitability of the product for a specific use. As the specific conditions-of-use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.