



MOBIHEL®

Produced in HELIOS Tovarna barv, lakov in umetnih smol Količevo d.o.o.
Količevo 65, 1230 Domžale, Slovenia
T +386 1 722 40 00
F +386 1 722 43 10
E info@helios.si
www.helios.si

TECHNICAL DATA SHEET









MOBIHEL PE putty for plastics

Use: *Two-component polyester levelling out mass with a relatively coarse structure, good elasticity and sand-blasting to even out irregularities on plastic parts e.g. bumpers, mirror covers, rails.....
It is not porous (it does not cause holes after sand-blasting) and will not be reduced with time.*

Surface: *- Clean plastics thoroughly with MOBIHEL cleaner for plastics low VOC and spray MOBIHEL Primer for plastics low VOC*

Colour shade: *grey*

FOR PROFESSIONAL USE ONLY!

	<p><i>Pot life</i> 4 – 6 min. / 20°C</p>
	
	<p>20 – 30 min. / 20°C</p>
	<p>5 min.</p>
	<p>P 150 - 220</p>
	<p>FURTHER TREATMENT: All 2K sealers from MOBIHEL programme.</p>
	<p>EU limit value VOC for this type of products (category II B (a)) in the form, which is ready for application is 250 g/l VOC of this product, prepared for use is 170 g/l.</p>
	<p>1 year</p>